

Bigfoot Construction Equipment, Inc.

3 Strand Poly-Dacron Combination Rope

High tensile polyester fiber bound over polypropylene core yarns. Good abrasion resistance and high strength. 5/8" diameter meets ANSI & OSHA standards for fall protection ropes.



3 Strand Poly-Dacron Combination Rope

Part Number	Diameter (in.)	Length (ft.)	Minimum Break Strength (lbs.)	Approximate Density (lbs./100 ft.)	Approximate Package Weight (lbs.)
PDTW080600	1/4	600	1,300	1.7	10.2
PDTW081200	1/4	1,200	1,300	1.7	20.4
PDTW120600	3/8	600	4,047	3.6	21.6
PDTW121200	3/8	1,200	4,047	3.6	43.2
PDTW160600	1/2	600	5,875	6.5	39.0
PDTW161200	1/2	1,200	5,875	6.5	78.0
PDTW200600	5/8	600	8,946	9.5	57.0
PDTW201200	5/8	1,200	8,946	9.5	114.0
PDTW240600	3/4	600	10,192	12.5	75.0
PDTW241200	3/4	1,200	10,192	12.5	150.0
PDTW320600	1	600	17,000	22.0	132.0
PDTW360600	1-1/2	600	34,000	46.0	276.0
PDTW400600	2	600	62,000	82.0	492.0

Call (888) 743-7320 to Order Today

